

Enclosed Switch-Fuse - Disconnectors

- ✓ 3 switched poles* + BS 88 fuse links + Neutral link (unswitched)
- ✓ 4 switched poles* + BS 88 fuse links + copper link (switched)

Enclosed Switch - Disconnectors

- ✓ 3 switched poles* + Neutral link (unswitched)
- ✓ 4 switched poles*

*Note

Regulation 537.1.1 Note 1

Table 537.4(3) Suitable for on-load switching and isolation in TN-C-S and TN-S systems meeting the requirements of Regulation 461.2

TT systems 4 pole switching

- ✓ - Ratings up to 630A
- ✓ - Padlockable handle
- ✓ - Indoor Installation
- ✓ - IP65 Steel Enclosure
- ✓ - Door Interlocked
- ✓ - Gland Plate Entry
- ✓ - UK Assembly

Switch supplied with 1 set of incoming terminal shrouds.

If you require additional terminal shrouds, please order separately.

Refer to the [Accessories](#) page.



Product Standard: EN60947-3

3 Pole Enclosed Switch-Fuse-Disconnectors			
Ratings @ 35° C for Cable < 70° C and CSA*			
Refer to Technical Data for additional information			
Poles	AC22A Amps	Cable csa mm ²	Reference
3	20	2.5	ASF-3020
3	32	6	ASF-3032
3	63	16	ASF-3063
3	100	50	ASF-3100
3	160	70	ASF-3160
3	200	95	ASF-3200
3	250	120	ASF-3250
3	400	240	ASF-3400
3	630	2 x 185	ASF-3630

3 Pole Enclosed Switch-Disconnectors			
Ratings @ 35° C for Cable < 70° C and CSA*			
Refer to Technical Data for additional information			
Poles	AC22A Amps	Cable csa mm ²	Reference
3	20	4	AS-3020
3	32	6	AS-3032
3	63	16	AS-3063
3	100	35	AS-3100
3	160	70	AS-3160
3	200	95	AS-3200
3	250	120	AS-3250
3	400	240	AS-3400
3	630	2 x 185	AS-3630

4 Pole Enclosed Switch-Fuse-Disconnectors				
Ratings @ 35° C for Cable < 70° C and CSA*				
Refer to Technical Data for additional information				
Poles	AC22A Amps	Cable csa mm ²	Reference	Neutral Pole Position
4	63	16	ASF-4063	On the Left
4	100	50	ASF-4100	On the Left
4	160	70	ASF-4160	On the Left
4	200	95	ASF-4200	On the Right
4	250	120	ASF-4250	On the Right
4	400	240	ASF-4400	On the Right
4	630	2 x 185	ASF-4630	On the Right

*The position of the neutral pole cannot be changed
The neutral pole copper link must not be replaced with a fuse link*

4 Pole Enclosed Switch-Disconnectors				
Ratings @ 35° C for Cable < 70° C and CSA*				
Refer to Technical Data for additional information				
Poles	AC22A Amps	Cable csa mm ²	Reference	Neutral Pole Position
4	100	50	AS-4100	On the Left
4	160	70	AS-4160	On the Left
4	200	95	AS-4200	On the Left
4	250	120	AS-4250	On the Left
4	400	240	AS-4400	On the Left
4	630	2 x 185	AS-4630	On the Left

The position of the neutral pole cannot be changed

*** Note:**

The cable csa above is based on the requirements of 60947-3 - maximum conductor temperature 70° C.

Refer to regulation 523 Current carrying capacity requirements for cables.

Have a question? Please contact us today

Tel: 01628 829133 email: sales@doepke.co.uk

Doepke UK Ltd